MANURHIN K'MX 916CLEVER

Innovative technology





MANURHIN K'MX 916CLEVER

Aluminium EN AW 6061	Brass CuZn39Pb3	Automatic steel 1.0737	Stainless steel 1.4301
24 sec.	25 sec.	29 sec.	47 sec.



MANURHIN K'MX 916CLEVER

Aluminium EN AW 6061	Brass CuZn39Pb3	Automatic steel 1.0737	Stainless steel 1.4301
19 sec.	22 sec.	27 sec.	48 sec.



MANURHIN K'MX 916CLEVER

Aluminium EN AW 6061	Brass CuZn39Pb3	Automatic steel 1.0737	Stainless steel 1.4301
25 sec.	30 sec.	41 sec.	59 sec.



MANURHIN K'MX 916CLEVER

Aluminium EN AW 6061	Brass CuZn39Pb3	Automatic steel 1.0737	Stainless steel 1.4301
29 sec.	30 sec.	35 sec.	56 sec.



MANURHIN K'MX 916CLEVER

Aluminium EN AW 6061	Brass CuZn39Pb3	Automatic steel 1.0737	Stainless steel 1.4301
25 sec.	27 sec.	32 sec.	43 sec.



MANURHIN K'MX 916CLEVER

Aluminium EN AW 6061	Brass CuZn39Pb3	Automatic steel 1.0737	Stainless steel 1.4301
38 sec.	39 sec.	42 sec.	81 sec.

Cycle time is calculated for standard cutting tools, without any special technology, without high pressure coolant and primary with focus on optimal longevity of used cutting tools.

TAJMAC-ZPS

MANURHIN K'MX®